



Construction :

- | | |
|-------------------|---|
| 1. Conductor | : Stranded annealed copper wire |
| 2. Insulation | : PVC |
| 3. Identification | : Printed White number on the surface of Black insulation |
| 4. Sheath | : Mylar tape |
| 5. Filler | : PVC Black color |
| | : PP yarn and/or PVC |

0.6/1KV CVV IEC 502 (2-30 CORE)

Number of Core จำนวนแกน	Cross Sectional Area (sq.mm.) ขนาดพื้นที่หน้าตัด (ตร.มม.)				
	Price (Baht/Meter) ราคา (บาท/เมตร)				
	0.75 SQMM.	1 SQMM.	1.5 SQMM.	2.5 SQMM.	4 SQMM.
2	34.30	36.50	40.30	54.50	74.80
3	38.10	41.90	49.30	68.80	94.30
4	47.80	49.40	59.80	85.30	125.60
5	58.30	65.00	76.20	109.20	152.50
7	68.80	78.50	94.30	137.80	198.90
9	91.30	106.20	129.40	183.80	263.20
10	98.70	114.40	140.40	201.80	290.00
12	109.90	128.60	158.50	233.20	342.20
14	121.80	140.50	176.40	261.60	386.10
16	130.80	153.90	195.00	292.50	445.90
19	148.70	175.80	224.50	341.90	517.40
21	167.70	198.90	250.90	379.60	572.00
24	185.90	219.70	280.80	439.40	647.40
27	206.70	239.20	312.40	484.40	722.20
30	221.00	261.30	341.90	531.70	795.60