



- Construction :**
- | | |
|-----------------|-----------------------------------------------------------|
| 1. Conductor | : Stranded annealed copper wire |
| 2. Insulation | : PVC Black color |
| Identification | : Printed White number on the surface of Black insulation |
| 3. Binding tape | : Mylar tape |
| 4. Inner sheath | : PVC Black color |
| 5. Shield | : Annealed copper tape |
| 6. Binding tape | : Mylar tape |
| 7. Outer sheath | : PVC Black color |
| 8. Filler | : PP yarn and/or PVC or other |

0.6/1KV CVV-S IEC 502 (2-30 CORE)

Number of Core จำนวนแกน	Cross Sectional Area (sq.mm.) ขนาดพื้นที่หน้าตัด (ตร.มม.)				
	Price (Baht/Meter) ราคา (บาท/เมตร)				
	0.75 SQMM.	1 SQMM.	1.5 SQMM.	2.5 SQMM.	4 SQMM.
2	62.80	65.65	73.20	91.30	121.20
3	68.80	74.80	83.70	109.00	145.60
4	80.60	85.30	98.80	130.00	176.40
5	94.30	101.70	116.60	158.60	209.30
7	109.20	119.60	141.70	191.10	262.60
9	133.90	147.90	171.60	239.20	326.30
10	146.90	159.90	187.20	261.30	366.60
12	158.60	174.20	209.30	291.20	406.90
14	174.20	195.00	230.10	322.40	475.80
16	187.20	211.90	254.80	361.40	533.00
19	209.30	239.20	283.40	416.00	598.00
21	228.80	258.70	309.40	470.60	676.00
24	254.80	289.90	349.70	530.40	773.50
27	278.20	313.30	383.50	581.10	847.60
30	295.10	339.30	425.10	633.10	926.90