

# HITACHI



## HITACHI FUSE - FREE BREAKER



M - SERIES FOR 3 PHASE INDUCTION MOTOR 400 - 440V AC

FRAME	RATED CURRENT	NEMA (Sym) 480V AC INTERRUPTING	MOTOR CAPACITY	PRICE
	( A )	( KA )	( KW )	
MS-50SB	2.3	2.5	0.75	2,400.-
MS-50SB	4.2	2.5	1.5	2,400.-
MS-50SB	5.6	2.5	2.2	2,400.-
MS-50SB	9	2.5	3.7	2,400.-
MS-50SB	14	2.5	5.5	2,400.-
MS-50SB	16	2.5	7.5	2,400.-
MS-50SB	25	2.5	11	2,400.-
MS-50SB	33	2.5	15	2,400.-
MF-60RB	40	7.5	18.5	2,800.-
MF-60RB	45	7.5	22	2,800.-
MF-100RB	60	14	30	-
MF-100RB	75	14	37	-
MF-100RB	90	14	45	-

## HITACHI LEAKAGE BREAKERS

EARTH LEAKAGE BREAKERS E - SERIES; R - SERIES

SPEC. TYPE	POLE	RATED CURRENT ( A )	SENSITIVITY ( MA )	IC(KA) JIS 415V	DIMENSION			PRICE
					H	W	D	
ET-30E	2P	15, 20, 30	30	220V 1.5	70	68	40	1,500.-
EX50C	3P	15, 20, 30, 40, 50	30/100/200/500	10	130	75	60	4,200.-
EX100B	3P	60, 75, 100	30/100/200/500	10	130	75	60	7,500.-
EXK225	3P	125, 150, 175, 200, 225	30/100/200/500	15	165	105	60	9,000.-
RX50	3P	15, 20, 30, 50	30/100/200/500	50	150	90	103	8,500.-
RX100	3P	60, 75, 100	30/100/200/500	50	150	90	103	8,000.-
RX100	4P	100	30/100/200/500	50	150	120	103	16,000.-
RX225B	3P	125 -225 Adjustable	30/100/200/500	50	165	105	103	16,000.-