



LY-01FL

For Non Insulated 90° flag terminals



LY-02FL

For Non Insulated 90° flag terminals



LY-03FL

For Insulated 90° flag terminals



LY-04FL

For Tab 90° flag terminals



LY-05FL

For Tab 90° flag terminals



LY-06FL

For Non Insulated 90° flag terminals



LY-10FL

For Non Insulated 90° flag terminals



LY-16FL

For Non Insulated 90° flag terminals



คีมย้ำหางปลารถยนต์ 90° (Flag Terminals)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
LY-01FL	0.5-1	20-18	0.60	230	1,160.-
	1.5-2.5	16-14			
LY-02FL	0.5-1	20-18	0.60	230	1,350.-
	1.5-2.5	16-14			
LY-03FL	0.5-1	20-18	0.60	230	1,350.-
	1.5-2.5	16-14			
LY-04FL	0.5-1	20-18	0.60	230	1,500.-
LY-05FL	1.5-2.5	16-14	0.60	230	1,500.-
LY-06FL	2.5-6	14-10	0.60	230	1,160.-
LY-10FL	10	8	0.60	230	1,280.-
LY-16FL	16	6	0.60	230	1,280.-

คีมย้ำหางปลารถยนต์

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
LY-03BM	0.5-6	20-10	0.60	230	1,480.-
LY-48B	0.14-2.5	26-14	0.60	230	1,350.-
LY-63B	0.25-6	22-10	0.60	230	1,350.-



LY-038M (SPECIAL MACHINE IT)

For unsulated receptacles and
tab 6.3mm width terminals



LY-48B

For unsulated receptacles
and tab 4.8mm, 2.8mm width terminals



LY-63B

For unsulated receptacles
and tab 6.3mm width terminals



Flag Terminals



คีมย้ำหางปลาชนิด (Flag Terminals)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
AN-03B48L	0.5-6	20-10	0.60	230	1,500.-
AN-03B63L	0.5-6	20-10	0.60	230	1,500.-
AN-48B48L	0.14-2.5	26-14	0.60	230	1,650.-
SN-02B48L	0.5-2.5	20-14	0.35	190	1,400.-



AN-03B48L

For unisulated receptacles and
Tab 4.8mm width terminals with locator



AN-03B63L

For unisulated receptacles and
Tab 6.3mm width terminals with locator



AN-48B48L

For unisulated receptacles and
Tab 4.8mm, 2.8mm width terminals with locator



SN-02B48L

For unisulated receptacles and
Tab 4.8mm, 6.3mm width terminals with locator

THAI-INTER
Electric Industries

(D-SUB MINIATURE CONTACTS)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
LY-145	0.14-0.5	20-25	0.2	163	900.-
LY-146	0.5-4	20-12	0.2	163	960.-



LY-145

4 Way to Crimping
Application

D-sub round barrel contacts, pins or sockets



LY-146

4 Way to Crimping
Application

D-sub round barrel contacts, pins or sockets



LY-02H1

For RG type cable



LY-05H

For RG type cable



LY-07H

For RG type cable



LY-510B

For RG type cable



LY-508C

For RG type cable



LY-518G

For RG type cable



LY-332

For RG type cable



LY-352

For RG type cable UTP and STP cable and CAT-5 round

คีมย้ำข้อต่อสาย RG

รุ่น (Model)	6.5mm	5.4mm	3.25mm	2.0mm	1.72mm	1.0mm	ราคา (฿)
LY-02H1	58, 59, 62, 8X, 140, 141, 174, 210, 223, 303, 400, FIBER OPTIC, BELDEN 8279						1,080.-
LY-05H	55, 58, 59, 62, 5, 6, 21, 140, 141, 142, 143, 210, 212, 222, 223, 303, 304, 400 BELDEN 8279, 8281, 9231, 9141	8.1mm	6.5mm	5.4mm	2.6mm	1.72mm	1,200.-
LY-07H	CATV F CONNECTORS, RG59, RG6	8.9mm	8.1mm	6.5mm			1,150.-

คีมย้ำข้อต่อสาย RG

รุ่น (Model)	Application Range	Weight Kg.	Length mm.	ราคา (฿)
LY-510B	RG-58, 59, 6 (C3, C4, C5) *F*, *BNC*, *RCA*	0.5	195	1,700.-
LY-508C	RG-59, 6 (C4, C5) *F*, *BNC*, *RCA*	0.55	230	2,800.-
LY-518G	RG-59, 6 (C4, C5) *F*, *BNC*, *RCA*	0.28	155	800.-

Connector Type	F	BNC	RCA	REC	MINI F
Connector Drawing					
Compressed Dimensions	20.3 x 0.2 mm	33.8 x 0.2 mm	31.8 x 0.2 mm	34.8 x 0.2 mm	34.8 x 0.2 mm

คีมปอกสายอัตโนมัติ (Coaxial Cable Stripper)

รุ่น (Model)	Details	ราคา (฿)
LY-332	รุ่น 2 ใบมีด สำหรับ ปอกสาย : - RG-58/59/62/6/6Q5/3C/4C/5C - "D" : 4, 6, 8 and 12 mm ²	400.-
LY-352	Strips outer jacket of UTP and STP cable and CAT-5 round Strip RG59/6/11/7coaxial cable Strips flat telephone cable With cable cutter	420.-



LY-03C

For insulated terminals and connectors 0.5-6mm²



LY-04C

For insulated terminals and connectors 0.14-6mm²



LY-10

For non insulated terminal 1.5-10mm²



LY-16

For non insulated terminal 2.5-16mm²



LY-13C

For close end terminal 0.5-6mm²



LY-28C

For close end terminal 4-10mm²



SN-4PT

For turned on contacts plug 0.14-4 mm²



SN-6PT

For turned on contacts plug 1.5-6 mm²



คีมย้ำหางปลาหุ้มฉนวน

รุ่น (Model)	Colour	Application Range		Weight Kg.	Length mm.	ราคา (฿)
		mm ²	AWG			
LY-03C	Red	0.5-1.5	20-16	0.6	230	1,080.-
	Blue	2.5	14			
	Yellow	4-6	12-10			
LY-04C	Green	0.14-0.5	26-20	0.6	235	1,150.-
	Red	0.75-1.5	18-16			
	Blue	2.0-2.5	14			
	Yellow	3.5-6	12-10			

คีมย้ำหางปลาเปลือย

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
LY-10	1.5-10	16-8	0.60	230	1,080.-
LY-16	2.5-16	14-5	0.60	230	1,100.-

คีมย้ำหัวนมปิด (Close End)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
LY-13C	0.5-6	20-10	0.60	230	1,080.-
LY-28C	4-10	12-8	0.60	230	1,200.-

คีมย้ำเทิร์นคอนแทคพ러그 (Turned Contact Plug)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
SN-4PT	0.14-4	26-12	0.35	190	1,280.-
SN-6PT	1.5-6	16-10	0.35	190	1,280.-

คีมย้ำสลีปหุ้ม (Heat Shrink Terminal)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
BN-03C8	0.5-10	22-8	0.6	265	1,400.-



BN-03C8

For heat shrink terminal applicable range: 0.5-10mm² AWG22-8





LY-04WF

For wire ferrules, end sleeves 0.5-4mm²



LY-06WF

For wire ferrules, end sleeves 0.5-6mm²



LY-16WF

For wire ferrules, end sleeves 6-16mm²



LY-26TW

For twin end sleeves applicable range 2x0.5, 2x0.75, 2x1, 2x1.5, 2x2.5, 2x4, 2x6mm²



LY-35WF

For wire ferrules, end sleeves 10-35mm²



LY-50WF

For wire ferrules, end sleeves 25-50mm²



LY-06WF2C

for Pre Insulated Terminal 0.5 - 2.5 mm² & AWG 20-14
for End Sleeves 0.5 - 6 mm² & AWG 20-10



คีมย้ำสลีปเข้าปลายสาย (Wire ferrules, End sleeves)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
LY-04WF	0.5-4	20-12	0.60	230	1,100.-
LY-06WF	0.5-6	20-10	0.60	230	1,100.-
LY-16WF	6-16	10-6	0.60	230	1,100.-
LY-26TW	2x0.5-2x6	2x20-2x10	0.60	230	1,350.-
LY-35WF	10-35	8-2	0.60	240	1,450.-
LY-50WF	25-50	3-0	0.60	240	1,550.-

คีมย้ำสลีปเข้าปลายสาย (Pre-Insulated Terminal, End sleeves)

รุ่น (Model)	Application Range	Weight Kg.	Length mm.	ราคา (฿)
LY-06WF2C	for Pre Insulated Terminal 0.5 - 2.5 mm ² AWG 20-14	0.60	230	1,400.-
	for End Sleeves 0.5 - 6 mm ² AWG 20-10			

คีมย้ำสลีปเข้าปลายสาย (Crimping Plier)

รุ่น (Model)	Application Range	Details	ราคา (฿)
ES-16A	0.5-16mm ²	พร้อมชุดสลีปเข้าปลายสาย	600.-

สลีปเข้าปลายสาย

0.5 mm ²	0.75 mm ²	1mm ²	1.5mm ²	2.5mm ²	4 mm ²	6 mm ²	10 mm ²	16mm ²
25 pcs	25 pcs	25 pcs	20 pcs	15 pcs	10 pcs	10 pcs	5 pcs	5 pcs



ES-16A



LY-25NWF

For twin end sleeves 2x4, 2x6, 2x10 mm²For ferrules end sleeves 10-25 mm²

LY-35NWF

For twin end sleeves 2x6, 2x10, 2x16 mm²For ferrules end sleeves 16-35 mm²

LY-50NWF

For twin end sleeves 2x16, 2x25 mm²For ferrules end sleeves 35-50 mm²

KH-95WF

For wire ferrules end sleeves

from(AWG 1/0-3/0) 50-95mm²

KH150WF

For wire ferrules end sleeves

from(200mcm-300mcm) 120-150mm²

DL-6

For wire ferrules, end sleeves 0.08-6mm²

คีมย้ำลูปเข้าปลายสาย (Wire ferrules, End sleeves)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
LY-25NWF	10-25 2x4, 2x6, 2x10 mm ²	8-3	0.60	230	1,450.-
LY-35NWF	16-35 2x6, 2x10, 2x16 mm ²	6-2	0.60	230	1,450.-
LY-50NWF	35-50 2x16, 2x25 mm ²	2-0	0.60	230	1,550.-



คีมย้ำลูปเข้าปลายสาย (Wire ferrules, End sleeves)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
KH-95WF	50-95	1/0-3/0	0.76	330	3,200.-
KH-150WF	120-150	250-300 mcm	1	380	3,550.-

คีมย้ำลูปเข้าปลายสาย (Wire ferrules, End sleeves)

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	mm ²	AWG			
DL-6	0.08-6	28-10	0.3	185	2,000.-
DL-10	0.75-10	18-8	0.3	185	2,000.-
DL-16	4-16	12-5	0.6	220	2,200.-



DL-10

For wire ferrules, end sleeves 0.75-10mm²

DL-16

For wire ferrules, end sleeves 4-16mm²

คีมย้ำหางปลาแบตเตอรี่ (Crimping Battery Connector: Din Tools)

รุ่น (Model)	Application Range			Weight Kg.	Length mm.	ราคา (฿)
	DIN mm ²	JIS mm ²	AWG			
HS-35B	16, 35	14, 38	6, 2	2.5	540	5,400.-



HS-35B



หางปลาแบตเตอรี่

คีมหุ้มฉนวนกันไฟฟ้า

1000Vac

รุ่น (Model)	Details	Length	ราคา (฿)
CP-127V	คีมปากจิ้งจก	180mm(7")	480.-
CP-128V	คีมปากจิ้งจก	200mm(8")	500.-
LN-116V	คีมปากแหลม	160mm(6")	480.-
LN-118V	คีมปากแหลม	200mm(8")	500.-
DP-106V	คีมปากเฉียง	160mm(6")	480.-



CP-127V 7"
Combination Pliers



CP-128V 8"
Combination Pliers



LN-118V 8"
Long nose Pliers



LN-116V 6"
Long nose Pliers



DP-106V 6"
Diagonal Cutting



SU-2

For non-insulated terminal 0.25-2.5 mm²



SU-6

For non-insulated terminal 0.75-6 mm²



SU-8

For non-insulated terminal 1.25-8 mm²



SU-9

For non-insulated terminal 1.25-8 mm²



SU-16

For non-insulated terminal 1.25-14 mm²



SU-13

For Close end terminal 0.5-6 mm²



SU-22

For non-insulated terminal 5.5-22 mm²



SU-38

For non-insulated terminal 5.5-38 mm²

คีมย้ำหางปลาเปลี่ยน หัวตัววัด

รุ่น (Model)	Application Range			Weight Kg.	Length mm.	ราคา (฿)
	JIS mm ²	DIN mm ²	AWG/MCM			
SU-2	0.25 - 2.5	0.25 - 2.5	20 - 14	0.24	190	900.-
SU-6	0.75 - 5.5	0.75 - 6	18 - 10	0.24	190	900.-
SU-8	1.25 - 8	1.5 - 10	16 - 8	0.43	260	940.-
SU-9	1.25 - 8	1.5 - 10	16 - 8	0.51	250	940.-
SU-16	1.25 - 14	1.5 - 16	16 - 5	0.51	285	1,200.-
SU-22	5.5 - 22	6 - 25	10 - 4	0.92	365	1,900.-
SU-38	5.5 - 38	6 - 35	10 - 2	0.92	365	2,200.-
SU-13	0.5 - 6	0.5 - 6	20 - 10	0.51	285	1,160.-



KH-8

For non-insulated terminal 1.25-8 mm²

KH-14

For non-insulated terminal 5.5-14 mm²

KH-16

For non-insulated terminal 1.25-14 mm²

KH-22

For non-insulated terminal 5.5-22 mm²

KH-38

For non-insulated terminal 5.5-38 mm²

KH-120

For cable lug 10-95mm² With non-ratchet screw adjustment.

Design for aluminum (8AWG - c/o) and copper (8AWG-250MCM)



KH-170

For cable lug 10-150mm²

With non-ratchet screw adjustment. Design for aluminum (8AWG - 250MCM) and copper (8AWG-3000MCM)



THAI-INTER
Electric Industries

คีมย้ำหางปลาเปลี่ยน หัวตัว

รุ่น (Model)	Application Range			Weight Kg.	Length mm.	ราคา (฿)
	JIS mm ²	DIN mm ²	AWG/MCM			
KH-8	1.25, 2, 5, 8	1.5, 2, 6, 10	16-8	0.60	250	850.-
KH-14	5.5, 8, 14	6, 10, 16	10-6	0.60	270	980.-
KH-16	1.25, 2, 5.5, 8, 14	1.5, 2, 6, 10, 16	16-6	0.60	270	1,050.-
KH-22	5.5, 8, 14, 22	6, 10, 16, 25	10-4	0.92	365	1,700.-
KH-38	5.5, 8, 14, 22, 38	6, 10, 16, 25, 35	10-2	0.92	365	2,000.-
KH-120	8, 14, 22, 38, 60, 70, 80	10, 16, 25, 35, 50, 70, 95	8-25	2.80	558	3,800.-
KH-170	8, 14, 22, 38, 60, 70, 80, 100	10, 16, 25, 35, 50, 70, 95, 120, 150	8-30	3.80	660	7,000.-

For Non-Insulated Terminal with Moveable and Revolving Dies.



CT-38

For non-insulated terminal 10-35 mm²



CT-100

For non-insulated terminal 25-120 mm²



CT-80

For non-insulated terminal 10-95 mm²



CT-150

For non-insulated terminal 16-150 mm²

คีมย้ำหางปลาเปลี่ยน หัวตัวผู้

THAI-INTER
Electric Industries

รุ่น (Model)	Application Range			Weight Kg.	Length mm.	ราคา (฿)
	JIS mm ²	DIN mm ²	AWG/MCM			
CT-38	8, 14, 22, 38	10, 16, 25, 35	8 - 2	2.90	566	2,150.-
CT-80	8, 14, 22, 38, 60, 80	10, 16, 25, 35, 50-70, 95	8 - 3/0	3.90	638	3,100.-
CT-100	22, 38, 60, 80, 100	25, 35, 50-70, 95, 120	4 - 4/0	4.90	676	3,450.-
CT-150	14, 22, 38, 60, 80, 100, 150	16, 25, 35, 50, 70, 95, 120, 150	4-300	4.90	710	3,800.-



CX-1B

ราคาชุดละ 19,600 บาท

คีมย้ำหางปลาเปลี่ยนหัวทุกเหลี่ยม

- For cable lugs 25-300mm²
- The handle length can be adjustable
- ราคารวม die



รุ่น (Model)	C. Jaw Opening	Application Range Standard Copper Terminal	Standard Dies	Weight Kg.	Length Mm.
CX-1B	35 mm	25-300	With Die 25 35 50 70 95 120 150 185 240 300	4.50	980



HX-4

For non-insulated terminal 1-4 mm²



HX-10

For non-insulated terminal 2-10 mm²



HX-16

For non-insulated 6-16 mm²



HX-25B

For non-insulated terminal 6-25 mm²



HX-50B

For cable lugs 6-50 mm²

With moveable and revolving dies



HX-120B

For cable lugs 10-120 mm²

With moveable and revolving dies



HX-150B

For cable lugs 25-150 mm²

With moveable and revolving dies



HX-245B

For cable lugs 70- 240 mm² With moveable and revolving dies

The handle length can be adjustable.

คีมย้ำหางปลาเปลี่ยน หัวทกเหลี่ยม

รุ่น (Model)	Application Range		Weight Kg.	Length mm.	ราคา (฿)
	DIN mm ²	AWG/MCM			
HX-4	1-4 mm ²	18-12	0.60	250	1,100.-
HX-10	2-10 mm ²	14-8	0.60	270	1,200.-
HX-16	6-16 mm ²	10-6	0.60	270	1,280.-
HX-25B	6-25 mm ²	-	0.92	365	2,000.-
HX-50B	6-50 mm ²	-	1.30	390	3,480.-
HX-120B	10-120 mm ²	-	4.00	620	5,280.-
HX-150B	25-150 mm ²	-	4.00	620	5,280.-
HX-245B	70-240 mm ²	-	5.60	980	9,950.-